

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

SECTION 1. IDENTIFICATION

Product name : PURITY™ FG WO WHITE MINERAL OIL 90

Product code : SPFWO90P20, SPFWO90IBC, SPFWO90DRX, SPFWO90BLK, SPFWO90, PFWO90P20, PFWO90IBC, PFWO90DRX, PFWO90, PFWO90BLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc.
2310 Lakeshore Road West
Mississauga ON L5J 1K2
Canada
Telephone : 1-905-403-6785

Emergency telephone number

Emergency telephone number : CHEMTREC: 1-800-424-9300;
Poison Control Centre: Consult local telephone directory for emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Purity FG WO White Mineral Oil 90 is a highly refined white mineral oil intended for the food processing industry.

NSF 3H and H1 Registered.

This product complies with FDA 21 CFR 172.878 "White Mineral Oil" and 21 CFR 178.3620(a) regulations for direct food contact.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

None known.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	100

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : First aider needs to protect himself.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Foam
Water fog
Dry chemical
Dry powder
Carbon dioxide (CO₂)
Sand
- Unsuitable extinguishing media : Do NOT use water jet.
- Specific hazards during : Cool closed containers exposed to fire with water spray.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

firefighting

Hazardous combustion products : Carbon oxides (CO, CO₂), smoke and irritating vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : None known.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labelled containers.
To maintain product quality, do not store in heat or direct

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

sunlight.
Keep locked up or in an area accessible only to qualified or authorised persons.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters/ Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use.
Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : Clear and bright

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -15 °C (5 °F)

Boiling point/boiling range : No data available

Flash point : 266 °C (511 °F)
Method: Cleveland open cup

Fire Point : No data available

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated before ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.872 kg/l (15 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	103 cSt (40 °C)
	:	11.8 cSt (100 °C)
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Components:

White mineral oil (petroleum):

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labelled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EINECS : On the inventory, or in compliance with the inventory

AIC : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

ENCS	:	On the inventory, or in compliance with the inventory
ISHL	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TECI	:	On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PURITY™ FG WO WHITE MINERAL OIL 90

000003000599

Version 3.0

Revision Date 2025/03/20

Print Date 2025/03/20

Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds
Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518
Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285
Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2025/03/20
Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN